

Mini Vortex- NeoSwix Mini and Mini VT

#Cat: NB-12-4010A

Size: 1unit

#Cat: NB-12-4010B

Size: 1unit

The Mini Vortex is an essential unit in all labs which require quick mixing of individual test tubes (of varying sizes). NeoSwix Mini Series are:

Features :

- Tiny Vortex with small footprints
- Brushless DC motor for maintenance free long life
- Microprocessor controlled – delivers max speed even under varying load conditions
- Delivers speeds of 4500 RPM for thorough mixing & quick vortexing
- Adjustable speed (Mini VT only) - range between 2500 to 4500 RPM
- Orbital diameter of 4.5 mm
- Smart and Robust design – press activation with suspension
- Robust construction with Die cast Al. base and rubber pads for stable and silent operation
- Inbuilt counterbalance no walking issues
- Can be used inside fume hoods/cold rooms



NeoSwix Mini

Specification :

Model	NeoSwix Mini	NeoSwix Mini VT
Cat. #	NB-12-4010A	NB-12-4010B
Speed	4500 RPM	
Variable speed	No	Yes
Orbital Diameter	4.5 mm	
Motor Type	BLDC (Brushless DC)	
Max tube diameter	30 mm	
Max load Capacity	500 gm	
Press Activation	Yes	
Protection class	IP 43	
Inbuilt Counter balance	Yes	
Power Supply	Universal (90 to 230V, 50 / 60 Hz.)	
Dimensions (W x D x H)	100 x 100 x 67 mm	
Weight	0.55 kg	



NeoSwix Mini VT